


BUTTON DATA LOGGER

Self-Powered, Compact Size, USB Interface



The **Series BDL Button Data Logger** records temperature and humidity in applications where size and cost effectiveness are vital. Housed in a compact stainless steel case, the BDL is durable in hostile environments, while also being able to be inserted in small items and packages. The Series BDL-K Logger Kit includes 2 buttons, 2 magnets, an interface cable, and a plastic button holder.

FEATURES/BENEFITS

- Compact to fit in small areas and durable to work in hostile environments
- Self-powered unit gives no need for external power supply
- Magnetic mounting for quicker installation

APPLICATIONS

- Food processing verification
- HVAC system testing and balancing
- Pharmaceutical storage
- Transportation of temperature sensitive goods

| ACCESSORIES | |
|-------------|---|
| Model | Description |
| DL500-LITE* | Lite version Windows® operating system software |
| DL500** | Full version Windows® operating system software key |
| BDL-SIL | Weatherproof silicone housing (5 pk) |
| BDL-WALL | Wall mounting bracket (5 pk) |
| BDL-CLIP | Plastic button holder (5 pk) |
| BDL-1 | Temperature input data logger, no kit |
| BDL-2 | Temperature/humidity input data logger, no kit |

*Free download from website **Need lite version also

SPECIFICATIONS

| | |
|---|--|
| <p>Range: BDL-1: -40 to 185°F (-40 to 85°C); BDL-2: -4 to 185°F (-20 to 85°C), 0 to 100% RH.</p> <p>Memory Size: BDL-1: 2048 readings; BDL-2: 4096 temperature and 4096 humidity readings (low resolution), 2048 temperature and 2048 humidity readings (high resolution).</p> <p>Accuracy: BDL-1: ±1.5°F (±1°C) from -22 to 158°F (-30 to 70°C); BDL-2: ±0.9°F (±0.5°C) from 14 to 158°F (-10 to 70°C), ±5% RH.</p> <p>Resolution: BDL-1: 8 bit; BDL-2: 8 or 11 bit.</p> <p>Sampling Method: Stop on memory full or continuous recording.</p> | <p>Sampling Rate: BDL-1: Selectable from 1 to 255 min.; BDL-2: Selectable from 1 s to 24 hrs.</p> <p>Computer Requirements: Windows® 98, Windows® 2000, Windows® ME, Windows NT®, Windows® XP, and Windows Vista® operating system with 16 MB RAM, one free USB port.</p> <p>Power Requirements: 3 V lithium metal battery, internal, non-replaceable.</p> <p>Battery Life: BDL-1: 10 years (approx); BDL-2: 5 years (approx).</p> <p>Alarms: Programmable high/low.</p> <p>Interface: USB port (cable included with kits).</p> <p>Housing Material: 305 SS.</p> <p>Weight: 0.14 oz (4 g).</p> |
|---|--|

| MODEL CHART | | |
|-------------|----------------------|-----|
| Model | Input Type | Kit |
| BDL-K1 | Temperature | Yes |
| BDL-K2 | Temperature/humidity | Yes |

Windows®, Windows NT®, and Windows Vista® are registered trademarks of Microsoft Corporation.