


Dwyer

SERIES WE06 | W.E. ANDERSON™ BY DWYER

3-PIECE NPT STAINLESS STEEL V-BALL VALVES

V-Port, Vented Ball, Electric or Pneumatic Actuators



WE06-DHD00-T



WE06-DDA01-T-AA01



WE06-CTI01-T-A



WE06-DDA01-T



WE06-DTD01-T-A



The **Series WE06 3-Piece NPT Stainless Steel V-Ball Valves** incorporate a V-port ball valve for impressive flow rates with minimal pressure drop. Quarter turn control ball valves are compact, lighter weight and much less expensive than comparable sized globe valves and segmented control valves. They also offer bubble tight shut off with zero leakage and can withstand high pressure drops. The 60° and 90° balls offer an equal percentage flow characteristic. W.E. Anderson's V-port ball valves have been designed to offer maximum flow characteristics that are substantially higher than comparably sized globe valves. The natural flow pattern of ball valves increases flow rates and in many applications valves smaller than pipeline size can be used. Limit switches can be mounted directly to the valves allowing for remote position indication.

The Series WE06 can be configured with an electric or pneumatic actuator. Electric actuators are available in weatherproof or explosion-proof, a variety of supply voltages and two-position or modulating control.

Two-position actuators use the supply voltage to drive the valve open or close, while the modulating actuator accepts a 4-20 mA input for valve positioning. Actuators feature thermal overload protection and a permanently lubricated gear train.

The pneumatic double acting actuator uses an air supply to drive the valve open and closed. The actuator has two supply ports with one driving the valve open and the other driving the valve closed. Spring return pneumatic actuators use the air supply to open the valve and internally loaded springs return the valve to the closed position. Also available is the SV3 solenoid valve to electrically switch the air supply pressure between the air supply ports for opening and closing the valve.

BENEFITS/FEATURES

- The 60° and 90° balls offer an equal percentage flow characteristic
- Limit switches can be mounted to manual valves for remote monitoring
- Available with a variety of electric and pneumatic actuators

APPLICATIONS

- Gas or liquid flow control
- Ideal for bubble tight shut off at high pressure drops

SPECIFICATIONS

VALVE

Service: Compatible liquids and gases.

Body: 3-piece.

Line Sizes: 1/2 to 3".

End Connections: Female NPT.

Pressure Limits: 20" Hg to 1000 psi (-0.7 to 69 bar) up to 250°F.

Wetted Materials: Body and ball: 316 SS (CF8M); Stem: 316 SS; Seat: RTFE/PTFE; Seal, washer, and packing: PTFE.

Temperature Limits: -20 to 392°F (-29 to 200°C).

Other Materials: O-ring: Fluoroelastomer; Handle: 304 SS; Washer: 301 SS; Stem nut, Locking device, Gland ring: 304 SS; Handle sleeve: PVC.

Agency Approvals: Meets the technical requirements of EU Directive 2011/65/ EU (RoHS II).

ACTUATORS

Pneumatic "DA" and "SR" Series

Type: DA series is double acting and SR series is spring return (rack and pinion).

Normal Supply Pressure: DA: 40 to 115 psi (2.7 to 7.9 bar); SR: 80 psi (5.5 bar).

Maximum Supply Pressure: 120 psi (8.6 bar).

Air Connections: DA01: 1/8" female NPT; DA02 to DA05: 1/4" female NPT; SR02 to SR07: 1/4" female NPT.

Housing Material: Anodized aluminum body and epoxy coated aluminum end caps.

Temperature Limits: -40 to 176°F (-40 to 80°C).

Accessory Mounting: NAMUR standard.

Electric "TD" and "MD" Series

Power Requirements: 110 VAC, 220 VAC, 24 VAC or 24 VDC (MD models not available in 24 VDC).

Power Consumption: See instruction manual.

Cycle Time (per 90°): TD01: 4 s; MD01: 10 s; TD02 and MD02: 20 s; TD03 and MD03: 30 s.

Duty Rating: 85%.

Enclosure Rating: NEMA 4X (IP67).
Housing Material: Powder coated aluminum.

Temperature Limits: -22 to 140°F (-30 to 60°C).

Electrical Connection: 1/2" female NPT.

Modulating Input: 4-20 mA.

Standard Features: Manual override, position indicator, and TD models come with two limit switches.

Electric "TI" and "MI" Series

Power Requirements: 110 VAC, 220 VAC, 24 VAC or 24 VDC.

Power Consumption: See instruction manual.

Cycle Time (per 90°): See instruction manual.

Duty Rating: See instruction manual.

Enclosure Rating: NEMA 7, designed to meet hazardous locations: Class I, Group C & D; Class II, Group E, F & G; Division I & II.

Housing Material: Powder coated aluminum.

Temperature Limits: -40 to 140°F (-40 to 60°C).

Electrical Connection: 1/2" female NPT.

Modulating Input: 4-20 mA.

Standard Features: Position indicator and two limit switches.

3-PIECE NPT STAINLESS STEEL V-BALL VALVES

V-Port, Vented Ball, Electric or Pneumatic Actuators

MODEL CHART							
Size	Cv (gal/min)		Popular Hand Operated Model	Popular Double Acting Pneumatic Model	Popular Spring Return Pneumatic Model	Popular NEMA 4X Two Position Electric (110 VAC) Model	Popular NEMA 4X Modulating Electric (110 VAC) Model
	60°	90°					
1/2"	7.9	9.1	WE06-CHD00-T	WE06-CDA01-T	WE06-CSR02-T	WE06-CTD01-T-A	WE06-CMD01-T-A
3/4"	13.6	14.2	WE06-DHD00-T	WE06-DDA01-T	WE06-DSR02-T	WE06-DTD01-T-A	WE06-DMD01-T-A
1"	22.3	29.1	WE06-EHD00-T	WE06-EDA02-T	WE06-ESR03-T	WE06-ETD01-T-A	WE06-EMD01-T-A
1-1/4"	31.5	53.7	WE06-FHD00-T	WE06-FDA02-T	WE06-FSR03-T	WE06-FTD01-T-A	WE06-FMD01-T-A
1-1/2"	46.2	75.5	WE06-GHD00-T	WE06-GDA03-T	WE06-GSR04-T	WE06-GTD02-T-A	WE06-GMD01-T-A
2"	104.7	138.4	WE06-HHD00-T	WE06-HDA03-T	WE06-HSR05-T	WE06-HTD02-T-A	WE06-HMD02-T-A
2-1/2"	147.5	220.3	WE06-IHD00-T	WE06-IDA04-T	WE06-ISR07-T	WE06-ITD03-T-A	WE06-IMD03-T-A
3"	209.1	308.3	WE06-JHD00-T	WE06-JDA05-T	WE06-JSR07-T	WE06-JTD03-T-A	WE06-JMD03-T-A

MODEL CHART - HAND OPERATED AND PNEUMATIC ACTUATOR								
Example	WE06	-CSR02	-T	-N	N	09	WE06-CSR02-T-NN09	
Series	WE06						316 SS 3-piece NPT	
Size and Actuator	CHD00						1/2" hand operated	
	DHD00						3/4" hand operated	
	EHD00						1" hand operated	
	FHD00						1-1/4" hand operated	
	GHD00						1-1/2" hand operated	
	HHD00						2" hand operated	
	IHD00						2-1/2" hand operated	
	JHD00						3" hand operated	
	CDA01						1/2" double acting	
	DDA01						3/4" double acting	
	EDA02						1" double acting	
	FDA02						1-1/4" double acting	
	GDA03						1-1/2" double acting	
	HDA03						2" double acting	
	IDA04						2-1/2" double acting	
	JDA05						3" double acting	
	V-Ball Angle			T				60° v-ball
			N				90° v-ball	
Solenoid					N			No solenoid
					A			NEMA 4X NAMUR solenoid
Solenoid Voltage						N		No solenoid
						A		120 VAC
						B		220 VAC
						C		24 VAC
						D		24 VDC
Positioner and Switches							00	None
						01	42AD0 exp limit switch	
						02	45VD0 exp position transmitter	
						03	42AD0-B ATEX limit switch	
						04	42AD0-IE IECEX limit switch	
						06	QV-210101 poly limit switch	
						07	VPS and P1 prox switch	
						08	265ER-D5 positioner	
						09	285ER-D5 smart positioner	
Options						NO	Fail open spring return actuator	

ACCESSORIES	
Model	Description
VB-01	Volume booster

MODEL CHART - ELECTRIC ACTUATOR						
Example	WE06	-ETD01	-T	-B	WE06-ETD01-T-B	
Series	WE06				316 SS 3-piece NPT	
Size and Actuator	CTD01				1/2" NEMA 4X two-position	
	DTD01				3/4" NEMA 4X two-position	
	ETD01				1" NEMA 4X two-position	
	FTD01				1-1/4" NEMA 4X two-position	
	GTD02				1-1/2" NEMA 4X two-position	
	HTD02				2" NEMA 4X two-position	
	ITD03				2-1/2" NEMA 4X two-position	
	JTD03				3" NEMA 4X two-position	
	CMD01				1/2" NEMA 4X modulating	
	DMD01				3/4" NEMA 4X modulating	
	EMD01				1" NEMA 4X modulating	
	FMD01				1-1/4" NEMA 4X modulating	
	GMD01				1-1/2" NEMA 4X modulating	
	HMD02				2" NEMA 4X modulating	
	IMD03				2-1/2" NEMA 4X modulating	
	JMD03				3" NEMA 4X modulating	
	CTI01				1/2" exp two-position	
	DTI01				3/4" exp two-position	
	ETI02				1" exp two-position	
	FTI02				1-1/4" exp two-position	
GTI03				1-1/2" exp two-position		
HTI04				2" exp two-position		
ITI05				2-1/2" exp two-position		
JTI05				3" exp two-position		
V-Ball Angle			T		60° v-ball	
			N		90° v-ball	
	Actuator Voltage			A		110 VAC
				B		220 VAC
				C		24 VAC
			D		24 VDC	

REPAIR KIT	
Model	Valve Series and Size
VRK-10	WE06-1/2"
VRK-11	WE06-3/4"
VRK-12	WE06-1"
VRK-14	WE06-1-1/2"
VRK-15	WE06-2"
VRK-16	WE06-2-1/2"
VRK-17	WE06-3"
Parts List - Included in Kit	
1 PTFE thrust washer	
1 FKM O-ring	
2 PTFE stem packing	
2 PTFE seals	
2 RTFE seats	