


Dwyer


SERIES BTT-E/N

TEMPERATURE TRANSMITTER

Wall Mount for Building Applications



European style



North American style



The **Series BTT-E/N Temperature Transmitters** offer transmitter output signals with the same form and fit as our popular Series TE-E/N thermistor and RTD sensors for Building Automation and HVAC installations.

FEATURES/BENEFITS

- Transmitter signal offers reliable accuracy for installations with long wire runs between the transmitter and the receiver/controller

APPLICATIONS

- Room or indoor building space temperature monitoring

MODEL CHART		
Model	Housing	Output
BTT-N00-3	North American style	4-20 mA
BTT-N00-4	North American style	0-10 VDC
BTT-E00-3	European style	4-20 mA
BTT-E00-4	European style	0-10 VDC

SPECIFICATIONS

Temperature Sensor: Pt 1000 Ω RTD DIN Class A 0.00385Ω/°C.

Range: 32 to 122 °F (0 to 50 °C).

Temperature Limits: 32 to 122 °F (0 to 50 °C).

Accuracy: ±0.5 °C @ 25 °C.

Thermal Effect: ±0.01%/°C.

Response Time: 100 ms.

Power Requirements: 13-36 VDC for current models, 13-36 VDC or 16-28 VAC for voltage models.

Output Signal: 4-20 mA or 0-10 VDC (depending on model).

Electrical Connections: Screw terminal block.

Enclosure Rating: IP20.

Weight: 2.6 oz (73.7 g).

Agency Approvals: CE.

TEMPERATURE